

02/07/2008



Renner Italia S.p.A.
Via Ronchi inferiore, 34
40061 MINERBIO (BO)

EY---M494

Aluminium top coat paste

Main properties of the product:

<ul style="list-style-type: none"> • Simple introduction • Good stability 	<ul style="list-style-type: none"> • Good yield •
---	--

Versions:

F38	Fine	M38	Medium	C38	Course
------------	-------------	------------	---------------	------------	---------------

Recommended use:	<ul style="list-style-type: none"> • To pigment water-based top coats for indoor use 		
Using the product:	% for use EY---M494: from 5 to 10% max		
MIX WELL BEFORE USE		For 10 Kg	For 25 Kg
	Minimum	0.500 Kg	1.250 Kg
	Maximum	1,000 Kg	2.500 Kg
	The dose of use of the product must be established on the basis of the level of covering and opacity desired. .		

For further information regarding the use of water-based products in our range, please refer to the our guide.

Recommended top coats:

<ul style="list-style-type: none"> • YO-XXM700/-----, YO-XXM760/--NTR, YO-XXM750/--NTR, YO-XXM756/--NTR

General remarks

<ul style="list-style-type: none"> • Mix the product well before use. • If the product is stored in rooms with temperatures between 5 and 35°C, shelf life is 12 months. • It is necessary to have a <u>temperature that is not below 15°C</u> in the application phase for the product, support and environment. • The coating residues (washing water, booth water, waste coating) must be disposed of according to the Standards in force. Do not throw residues into the drain system.
--